

AMENDMENTS

The following listing of claims replaces all prior versions, and listings, of claims in the application:

1. (previously and currently amended) A packaging material comprising:
a substrate comprising at least one sheet of plastic material; the substrate having an inner surface and an outer surface;
a cold-seal cohesive coating on at least a portion of the an inner surface side of the substrate; and
an energy-cured release layer on ~~an outer side~~ the outer surface of the substrate, the release layer comprising a reacted-in slip agent, the release layer providing a surface for temporary adhesion of the cohesive without blocking of the cohesive upon removal of the cohesive from the release layer.
2. (currently amended) A packaging material according to claim 1, wherein the substrate comprises a laminate of at least two sheets of plastic material, one sheet being an outer sheet and the second sheet being an inner sheet.
3. (original) A according to claim 2, wherein an outer sheet of the laminate is clear, and further comprising printing on a surface between the outer sheet and an adjacent sheet.
4. (previously amended) A packaging material according to claim 1, further comprising printing on an outer surface of the substrate covered by the energy-cured release layer
5. (previously amended) A packaging material according to claim 1, wherein the cold-seal cohesive coating comprises natural rubber latex, styrene butadiene, isoprene or synthetic rubber.
6. (original) A packaging material according to claim 1, wherein the cold-seal cohesive coating comprises a minor proportion of acrylate or ethyl vinyl acetate.
7. (original) A packaging material according to claim 1, wherein the cold-seal cohesive coating is applied only over selected portions of the inner surface of the substrate.
8. (previously amended) A packaging material according to claim 1, wherein the energy cured release layer is an electron-beam cured coating.
9. (previously amended) A packaging material according to claim 1, wherein the energy cured release layer is a cross-linked epoxy acrylate coating.

10. (previously and currently amended) A package comprising:
at least one sheet of flexible packaging material comprising,
a substrate comprising at least one sheet of plastic material,
a cold-seal cohesive ~~coating~~ on one or more portions of an inner side of the
substrate, and
an energy-cured coating on an outer side of the substrate, the energy-cured
coating serving as a release layer for the cold-seal cohesive so that the cold-seal cohesive
remains attached to the inner side of the substrate and does not offset onto the energy-cured
coating when the material is unrolled after being stored in a roll;

wherein said package has at least one seam formed by ~~portions of~~ said cold-seal cohesive
~~coating on the one or more portions of the inner side of the substrate~~ cohering together.

11. (currently amended) A package according to claim 10, wherein the substrate
comprises a laminate of at least two sheets of plastic material forming an outer sheet and an inner
sheet.

12. (currently amended) A package according to claim 11, wherein an outer sheet of
the laminate is clear, and further comprising printing ~~on a surface~~ between the outer sheet and
the inner an adjacent sheet.

13. (currently amended) A package according to claim 10, further comprising
printing on an outer surface of the substrate which is covered by the energy-cured coating.

14. (previously amended) A package according to claim 10, wherein the cold-seal
cohesive ~~coating~~ comprises natural rubber latex, styrene butadiene, isoprene or synthetic rubber.

15. (original) A package according to claim 14, wherein the cold-seal cohesive ~~coating~~
comprises a minor proportion of acrylate or ethyl vinyl acetate.

16. (original) A package according to claim 10, wherein the cold-seal cohesive ~~coating~~
is applied only over selected portions of the inner surface of the substrate.

17. (previously and currently amended) A package according to claim 10, wherein said
cold-seal cohesive ~~coating~~ is applied to the inner surface of said substrate only on the portion of
the inner surface that forms the ~~at said at least one~~ seam.

18. (original) A package according to claim 10, wherein the energy cured coating is an
electron-beam cured coating.

19. (original) A package according to claim 10, wherein the energy cured coating is a cross-linked epoxy acrylate coating.

20 - 26. (previously cancelled)

27. (new) A packaging material comprising:

a substrate formed from a flexible plastic material, the substrate having an inner surface and an outer surface;

a cold-seal cohesive applied to one or more portions of the substrate surfaces, the cohesive adapted to seal the substrate portions together in forming the package;

an electron beam energy cured coating on the outer surface of the substrate, the coating serving as a release layer for the cohesive upon contact between the coating and the cohesive such that the cohesive temporarily adheres to the coating and releases upon removal without adversely affecting the adhesive properties of the cohesive;

ink printed in a pattern on the outer surface of the substrate and covered by the coating, the coating providing a glossy surface for the ink and the package; and

a reacted-in slip agent within the coating.